

NEWAGE

AN ISO 9001:2008 CERTIFIED COMPANY

SELF-PROPELLED SCISSOR LIFT



We believe in higher safety,
faster work & higher productivity.



Standard Features:

1. Battery Operated with Hydraulic Drive Motor
2. Extension Platform to reach the site quickly
3. Fork Lift Slots for easy transportation
4. Automatic display of fault code for easy maintenance
5. Low Noise, Non-Pollution and Strong Adaptability for various using sites

Safety Features:

1. Auxiliary Lowering Device
2. Anti-burst System
3. Emergency Stop Button
4. Tilting Protection System
5. Charging Protection System
6. Automatic Pothole Protection
7. Automatic Braking System
8. Buzzer and Horn

Specification

Model	MX600SN	MX800SN	MX800S	MX1000S	MX1200S	MX1400S
Working height max (m)	8	10	10	12	13.8	16
Platform height max (m)	6	8	8	10	11.8	14
Slide-out platform extension deck (m)	0.9	0.9	0.9	0.9	0.9	0.9
Lift capacity (kg)	380	230	450	320	230	227
Lift capacity (kg) (Platform extended)	113	113	113	113	113	113
Weight (kg) CE / AUS Standard	1945	2100	2175	2468	2830	3320
Platform size (LxW) (m)	2.27*0.81	2.27*0.81	2.27*1.12	2.27*1.12	2.27*1.12	2.64*1.12
Platform length extended (m)	3.17	3.17	3.17	3.17	3.17	3.17
Stowed size (LxW) (m)	2.43*0.81	2.43*0.81	2.43*1.15	2.48*1.15	2.43*1.15	2.84*1.39
Stowed height (m)	2.18	2.3	2.31	2.42	2.55	2.59
Platform height (m) (guardrails folded)	1.85	1.87	1.76	1.91	2.03	2.05
Wheelbase (m)	1.87	1.87	1.87	1.87	1.87	2.22
Length of the machine with platform extended (m)	3.17	3.17	3.17	3.17	3.17	3.17
Hydraulic system capacity (L)	20	20	20	20	20	20
Gradeability	0.25	0.25	0.25	0.25	0.25	0.25
Ground clearance (m)	0.1	0.1	0.1	0.1	0.1	0.1
Ground clearance (m) (pothole guards deployed)	0.019	0.019	0.019	0.019	0.019	0.019
Turning radius (m) (inside)	0	0	0	0	0	0
Turning radius (m) (outside)	2.1	2.2	2.2	2.2	2.2	2.7
Platform occupancy max	3	2	2	2	2	2
Raise / Lower time (s)	35s/25s	40s/30s	40s/30s	60s/40s	70s/45s	88s/60s
Drive speed (km/h) (stowed)	3	3	3	3	3	4
Drive speed (km/h) (raised)	1	1	1	1	1	0.8
Maximum Working Slope	2°/3°	2°/3°	2°/3°	2°/3°	1.5°/3°	2°/3°
Lifting Motor Power	3.3Kw	3.3Kw	3.3Kw	3.3Kw	4.5Kw	4.5Kw
Power source	4x6V ; 225Ah	4x6V ; 225Ah	4x6V ; 225Ah	4x6V ; 240Ah	4x6V ; 260Ah	2*12V ; 300Ah
Tire size (mm)	380*129	380*129	380*129	380*129	380*129	381*127
Charger	24V/30A	24V/30A	24V/30A	24V/30A	24V/30A	24V/25Ah



New Age Construction Equipment Engineering Company

Survey No. 275, Plot No. 4-B, Galaxy Industrial Estate,
Shapar (Veraval) Dist. Rajkot-360 002, Gujarat, India.

Ph. : +91 281 2451457 | **Fax :** +91 281 2480453 | **Cell :** +91 98244 16817

E-mail : info@newageindustries.in

Web : www.newageconstructionequipment.com | www.indiamart.com/newageindustries

For Service & Spares Contact: +91 95101 10771

NEWAGE
AN ISO 9001:2008 CERTIFIED COMPANY