

# ROPE SUSPENDED PLATFORM ZLP 250 & ZLP 800-1 (2.5)





For Painting Work



For Glass Cleaning



For Wall Plastering



For Wall putty & Texture



We believe in higher safety, faster work & higher productivity.



### ROPE SUSPENDED PLATFORM ZLP 800-1 (2.5mtr.)

Model Type			ZLP 250	ZLP 800-1 (2.5)
Rated Load			300 kg.	400 kg.
Lifting Speed			8.2 m/min	8.2 m/min
Max Lifting Height			100 Meter	100 Meter
Dimension of platform (L*W*H)			1.2*0.69*1.18m	2.5m x 0.76m x 1.45m
Suspensi on mechanism	Front beam overhang		1.3 ~1.6 m	1.3 ~1.7 m
	Adjustable Height		1.15~1.6 m	1.15~1.75 m
Hoist	Model		LTD 8.0	LTD 8.0
	Lifting force		8 KN	8 KN
	Motor	Power	1.8 KW	1.8 KW
		Voltage	415 V, 50 HZ , 3 phase	415 V, 50 HZ, 3 phase
		Rotation speed	1400 R/Min.	1400 R/Min.
		Brake Torque	15.2 Nm	15.2 Nm
Safety lock	Туре		Tilt proof safety lock	Tilt proof safety lock
	Locking cable angel		-	3-8 degree
	Allowable impulsive force		20 KN	20 KN
Weight	Suspension platform including hoist, safety lock, electric control panel.		198 kg	270 kg
	Suspension mechanism		162 kg	400 kg
	Counterweight		500 kg	750 kg
	Whole machine weight without steel wire rope & power cable		860 kg	1420 kg
Wire rope	Туре		4X31SW+FC-8.6	4X31SW+FC-8.6
Platform type			Plastic coated	Plastic coated

#### **Our Valuable Customers**



























## ROPE SUSPENDED PLATFORM ZLP 250 (1.25mtr.)



### **Construction Equipment Engineering Company**

Survey No. 275, Plot No. 4-B, Galaxy Industrial Estate, Shapar (Veraval) Dist. Rajkot-360 002, Gujarat, India.

**Ph.**: +91 281 2451457 | **Fax**: +91 281 2480453 | **Cell**: +91 98244 16817

E-mail: in fo@newage industries.in

Web: www.newageconstructionequipment.com | www.indiamart.com/newageindustries

For Service & Spares Contact: +91 95101 10771



